



# 22" BNC FRAMELESS LED MONITOR

24/7/365 Operating Capability



The 22" BNC frameless LED monitor is designed to excel in 24/7 video surveillance applications. Delivering full HD resolution and 16.7 million colors, the monitor displays every detail with precision. HDMI and VGA inputs and a BNC input/output easily accommodate multiple devices and allow for BNC looping. The monitor also features source auto detection and quick touch scalability for quick setup.

## FEATURES

- 21.5" Diagonal Viewing Size
- 1920x1080P Full HD Resolution
- 178° Ultra-Wide Viewing Angle
- Source Auto Detection
- Low Blue Light Technology
- Quick Touch Scalability 16:9/4:3
- BNC, VGA, HDMI and Audio Inputs
- Includes VGA, Audio and Dual Power Cables (EU,UK)
- Two Built-In Speakers
- 36-Month Warranty
- Part #: CAP-22LED3-L
- UPC: 840049312234
- Length: 19.3" (490.2mm)
- Width: 8.6" (218.4mm)
- Height: 14.1" (358.1mm)
- Weight: 4.85 lbs. (2.2kg)
- UL Listed



## MONITEUR BNC À DEL SANS CADRE DE 22 PO

Capacité de fonctionnement 24/7/365



Le moniteur BNC à DEL sans cadre de 22 po est parfait pour les applications de vidéosurveillance en permanence. Grâce à une résolution HD intégrale et à ses 16,7 millions de couleurs, ce moniteur saura afficher tous les détails avec précision. Les entrées HDMI et VGA et une entrée/sortie BNC accueillir plusieurs appareils et permettre le bouclage BNC. Le moniteur est aussi doté de fonctionnalités de détection automatique de la source et de mise à l'échelle pour une configuration facile.

### CARACTÉRISTIQUES

- Dimensions d'achage diagonales de 21,5 po
- Résolution HD intégrale 1920x1080 p
- Grand angle de vue de 178°
- Détection automatique de la source
- Technologie à faible lumière bleue
- Mise à l'échelle Quick Touch 16:9/4:3
- Entrées BNC, VGA, HDMI et audio
- Comprend des Câbles audio, VGA et Câbles d'alimentation (EU,UK)
- Deux haut-parleurs intégrés
- Garantie de 36 mois
- N° de pièce : CAP-22LED3-L
- UPC : 840049312234
- Longueur : 19,3 po (490,2 mm)
- Largeur : 8,6 po (218,4 mm)
- Hauteur : 14,1 po (358,1 mm)
- Poids : 4,85 lb (2,2 kg)
- Homologué UL



| TECHNICAL SPECIFICATIONS           |                                                                                                            |
|------------------------------------|------------------------------------------------------------------------------------------------------------|
| Model                              | CAP-22LED3-L                                                                                               |
| Screen Diagonal Dimension (inches) | 21.5"                                                                                                      |
| Viewable Area W x H                | 18.8" x 10.2" (477.5mm x 259mm)                                                                            |
| LED Type                           | Edge LED                                                                                                   |
| Pixel Pitch (mm)                   | 0.2493mm x 0.241mm                                                                                         |
| Screen Maximum Resolution          | 1920x1080                                                                                                  |
| Display Resolutions                | 720x400; 640x480; 800x600; 1024x768; 1280x1024; 1366x768; 1920x1080                                        |
| Supported Input Resolutions        | 720x400; 640x480; 800x600; 1024x768; 1280x1024; 1366x768; 1920x1080                                        |
| Refresh Rate (hertz)               | 60Hz                                                                                                       |
| Color Depth (millions)             | 16.7 million colors                                                                                        |
| Brightness                         | 250 nits (250 cd/m²)                                                                                       |
| Auto Adjust                        | Yes                                                                                                        |
| Monitor Aspect Ratio               | 16:9                                                                                                       |
| Display Aspect Ratio               | OSD options: Full/4:3/Over Scan                                                                            |
| Horizontal TV Lines                | 1080                                                                                                       |
| Contrast Ratio                     | 4000:1SCR                                                                                                  |
| Response Time (ms)                 | 5 ms (GTG)                                                                                                 |
| View Angle H/V (degrees)           | 178° x 178°/CR>10                                                                                          |
| Digital Video Inputs               | HDMI up to 1920x1080                                                                                       |
| Analog Video In/Out                | VGA up to 1920x1080                                                                                        |
| Connectors                         | HDMI x 1, VGA x 1, BNC IN x 1, BNC OUT x 1, AUDIO OUT x 1                                                  |
| Audio Inputs (stereo)              | 1 x 3.5mm mini-jack                                                                                        |
| Speakers (watts)                   | 2 x 2 watts                                                                                                |
| Stand-by (watts)                   | <0.5 watt                                                                                                  |
| Power Consumption (watts)          | 16 watts typical                                                                                           |
| Monitor Body Dimensions            | 19.3" x 1.5" x 11" (490.2mm x 38.1mm x 279.4mm)                                                            |
| Dimensions Monitor+Stand           | 19.3" x 8.6" x 14.1" (490.2mm x 218.4mm x 358.1mm)                                                         |
| Panel Surface                      | Matte black                                                                                                |
| Case and Stand Material            | Plastic                                                                                                    |
| VESA Mounting Pattern (mm)         | 75mm x 75mm                                                                                                |
| Base/Stand Included                | Yes                                                                                                        |
| Base Tilt Angle                    | -5°-15°                                                                                                    |
| Weight Cabinet Only                | 4.08 lbs. (1.85kg)                                                                                         |
| Weight Cabinet+Base Stand          | 4.85 lbs. (2.2kg)                                                                                          |
| Power Supply (internal)            | AC 100-240V-50/60Hz 1.1A                                                                                   |
| Operating Temperature              | 0°C-40°C / 32°F-104°F                                                                                      |
| Storage Temperature                | -20°C-50°C / -4°F-122°F                                                                                    |
| Operating Humidity                 | 10-90%                                                                                                     |
| Accessories Included in the Box    | Dual power cable(EU,UK)/VGA cable/Audio cable/IR Remote<br>Stand support/Screws/Base of stand/User manuals |
| Mounting Screw Size (mm)           | M4-L8 mm/4pcs                                                                                              |
| Certifications                     | CE/FCC/RoHS/HDMI/UL/WEEE/REACH/UKCA                                                                        |
| Warranty                           | 36 Months                                                                                                  |